



If you listen very closely, you'll discover it's also a ventilation fan.

New styling and improved lighting make NuTone's industry leading Ultra Silent™ fan lights even better.

- Light output has been significantly increased, while using 14 fewer watts.
- Lighting design enhancements provide a brighter, broader flood-light effect.
- Improved light diffusion hides hotspots/bulbs.
- Convenient GU24 bulbs are readily available.
- A restyled, low-profile grille on QTXEN models blends with any decor.
- Design and lighting improvements were made without increasing sound levels.

NEW HIGH PERFORMANCE LIGHTING USING LESS ENERGY



NuTone Ultra Silent™ Series Fan Lights. The Ultra Silent™ line represents the ultimate in bath fan solutions for today's homes. Select an Ultra Silent™ fan/light to bring elegance to any bath or powder room. Whether by sight or by sound, you'll barely notice the Ultra Silent™ line. Except, of course, when you need the right amount of ventilation and light at the touch of a switch.

QTXEN, QTREN and QTRN Fan/Light Features

- Nearly silent operation 0.3 to 1.4 sones
- 80 CFM to 150 CFM
- QTXEN models feature 6" ducting for superior performance
- QTREN and QTRN models feature 4" ducting
- QTXEN and QTREN models are Energy Star qualified
- Bright, energy efficient 36-watt fluorescent lighting (2-18 watt GU24 based bulbs) included with non-sensing QTXE and QTRE models**
- 100-watt lighting from an incandescent bulb on QTRN models
- 4-watt nightlight on all models
- QTXEN, QTREN and Housing Packs include hanger bar system for fast and flexible installation for all types of construction
- UL Listed for use over tub or shower when installed in a GFCI protected branch circuit
- HVI Certified
- Motor engineered for continuous operation
- Type IC
- Fits 2" x 8" ceiling construction

QTXEN Models

NEW GRILLE STYLING



QTREN Models



QTRN Models



Model	CFM	Sones	Light/ Nightlight	Energy Star	Title 24 Compliant	Duct
QTXEN080FLT	80	0.3	36W [♦] / 4W	Yes	Yes	6" ▲
QTXEN110FLT	110	0.7	36W [♦] / 4W	Yes	Yes	6" ▲
QTXEN150FLT	150	1.4	36W [♦] / 4W	Yes	Yes	6" ▲
QTREN080FLT	80	0.8	36W [♦] / 4W	Yes	Yes	4"
QTREN110FLT	110	1.3	36W [♦] / 4W	Yes	Yes	4"
QTRN080L	80	1.0	100W [■] / 4W	—	—	4"
QTRN110L	110	1.5	100W [■] / 4W	—	—	4"

Energy Star fans use 65% less energy, on average, than standard models and may qualify for local utility rebates.
 ▲ See page 33 for 6" ducting (DT6W) product specifications.
 ■ Incandescent bulb. ♦ 2-18 watt GU24 based fluorescent bulbs.
 ** QTXEN110SFLT uses 1-42 watt pin-based bulb.

Fluorescent lighting is Title 24 compliant.



Project Packs Available for QTREN Models

To simplify installation, Project Packs are available with either four fan or fan/light housings only. When drywall work and painting is complete, the fan components needed to finish the job are available in single packs under separate model numbers. These finish kits include the motor plate, motor, wheel and grille. See the matrix below for Project Pack order information.

Project Pack	Kit number:	For model:
Four-pack of FAN/LIGHT housings only:	QTXRN000HL	
One-pack finish kits for FAN/LIGHT models:	QTREN080FLFT	QTREN080FLT
	QTREN110FLFT	QTREN110FLT

